













Type	Picture	Model	Resolution	Main Features	IRR
Bullet		HAC-HFW1000RM	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 20m, Smart IR 2.8mm fixed lens	950,000
Classic Bullet		HAC-HFW1000S	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	1,150,000
		HAC-HFW1200S	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	1,800,000
		HAC-HFW1220S	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	1,950,000
Long IR Range Bullet		HAC-HFW2221E	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 40m, Array LED, Smart IR 3.6mm fixed length	3,100,000
		HAC-HFW2401E	4MP WDR	1/3" 4Megapixel CMOS, 4MP 25/30fps@1080P, 25/30/50/60fps@720P ICR, IP67, 120db Ture WDR Max. IR Led length: 40m, Array LED, Smart IR 3.6mm fixed length	4,050,000
		HAC-HFW1200B	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Smart IR 3.6mm fixed lens	2,100,000
		HAC-HFW1220D	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 80m, Smart IR 3.6mm fixed lens	2,500,000
		HAC-HFW2221D	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 80m, Array LED, Smart IR 3.6mm fixed length	3,400,000
		HAC-HFW2401D	4MP WDR	1/3" 4Megapixel CMOS 4MP, 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 80m, Array LED, Smart IR 3.6mm fixed length	4,450,000
Vari-focal Bullet		HAC-HFW1100R-VF	720P	1/3" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.7-12mm manual vari-focal lens	2,200,000
		HAC-HFW1220R-VF-IRE6	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 60m, Array LED, Smart IR 2.7-12mm manual vari-focal lens	3,450,000
		HAC-HFW2221R-Z-IRE6	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 60m, Array LED, Smart IR 2.7-12mm motorized lens	6,000,000
Classic Dome		HAC-HDW1000M	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	950,000

Type	Picture	Model	Resolution	Main Features	IRR
Long IR Range Eyeball		HAC-HDW1200EM	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens All Metal	1,800,000
		 HAC-HDW1200EM-A	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	1,960,000
		 HAC-HDW1220EM-A	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	2,100,000
		 HAC-HDW2221EM-A	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length Bulit-in Mic, All Metal	3,200,000
		HAC-HDW2401EM	4MP WDR	1/3" 4Megapixel CMOS 4MP, 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length(6mm, 8mm optional)	3,990,000
Vari-focal Dome		HAC-HDBW1100R-VF-S3	720P	1/3" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Array LED, Smart IR 2.7-12mm manual vari-focal lens	2,200,000
		HAC-HDBW1220R-VF	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67, IK10 Max. IR Led length: 30m, Array LED, Smart IR 2.7-12mm manual vari-focal lens	3,400,000
		HAC-HDBW2221R-Z	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, IK10, 120db Ture WDR Max. IR Led length: 30m, Array LED, Smart IR 2.7-12mm motorized lens	5,900,000
Vari-focal Bullet		HAC-HFW3231E-Z	Starlight 1080P	1/2.8" 2.1Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Star Light, 120dB True WDR ICR, IP67 Max. IR Led length: 50m, Smart IR 2.7-12mm auto-iris motorized lens DC12V/AC24V, audio in, alarm in & out Tri-output	9,900,000
Vari-focal Dome		HAC-HDBW3231E-Z	Starlight 1080P	1/2.8" 2.1Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Star Light, 120dB True WDR ICR, IP67, IK10 Max. IR Led length: 50m, Smart IR 2.7-12mm auto-iris motorized lens DC12V/AC24V, audio in, alarm in & out Tri-output	9,900,000

**PAYTAKHTCCTV.COM** **فروشگاه پایتخت**

راههای ارتباطی ما: **021-66348327** / **09336765878** / **@Paytakhtcctv1** / تلگرام:



Type	Picture	Model	Resolution	Main Features	IRR
Indoor PTZ		SD22204I-GC	1080P 4x PTZ	1/2.7" 2Megapixel CMOS Powerful 4x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IP66, IK10	7,000,000
Speed Dome		SD49225I-HC	1080P 25x Starlight IR PTZ	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 100m IP66	20,000,000
		SD59230I-HC	2MP 30x Starlight IR PTZ	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 30x optical zoom Starlight technology 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 150m IP66	Call
		<b>NEW</b> SD59430I-HC	4MP 30x IR PTZ	1/3" 4Megapixel CMOS Powerful 30x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P IR distance up to 100m IP66	Call












Available on the  
**App Store**



GET IT ON  
**Google play**



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		<b>Penta-brid</b> XVR4104HS	<b>4ch 720P 25/30fps per channel</b> <b>8/16ch 720P 12/15fps per channel</b> 1 HDMI/1 VGA, 4/8/16ch Video in, 1 Audio in/1 Audio out, 1 RJ45(100M), 2 USB, 1 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive, 4+2/8+2 (up to 2MP)/16+2 IP camera input, up to 5Mp)	2,350,000
		<b>Penta-brid</b> XVR4108HS		3,550,000
		<b>Penta-brid</b> XVR4116HS		5,800,000
1U 2HDD		<b>Penta-brid</b> XVR4216AN	16ch 720P 12/15fps per channel 1 HDMI/1 VGA, 4/8/16ch Video in, 1 Audio in/1 Audio out, 1 RJ45(100M), 1 RS485, 2 USB, 2 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive, 16+2 IP camera input, up to 5Mp)	9,300,000
		<b>Tribrid</b> HCVR4232AN-S3		16,000,000
Compact 1U 1HDD		<b>Penta-brid</b> XVR5104HS	4/8 ch 1080P 12/15fps per channel, 720P realtime 1 HDMI/1 VGA, 4/8ch Video in, 1 Audio in/1 Audio out, 1 RJ45(100M), 1 RS485, 2 USB, 1 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive, 4+2/8+4 8 IP camera input, up to 5Mp)	3,990,000
		<b>Penta-brid</b> XVR5108HS		6,600,000
1U 2HDD		<b>Penta-brid</b> XVR5216A	16ch 1080P 12/15fps per channel, 720P realtime 1 HDMI/1 VGA, 1 RJ45(100M), 4 Audio in/1 Audio out, 16 Alarm in/3 Alarm out, 1 RS485, 2 USB, 2 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive, 16+8 IP camera input, up to 5Mp)	13,400,000
1.5U 4HDD		<b>AOC Penta-brid</b> XVR5416L	16ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV, 2 RJ45(1000M), 4 Audio in/1 Audio out, 8/16/16 Alarm in/6 Alarm out, 1 RS485, 3 USB, 4 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive, 8+4/16+8/16 IP camera input, up to 5Mp)	25,000,000
1U 2HDD		<b>AOC</b> HCVR5232AN-S3	32ch 1080P 12/15fps per channel, 720P realtime 1 HDMI/1 VGA, 1 RJ45(1000M), 4 Audio in/1 Audio out, 1 RS485, 2 USB, 2 HDD, Tribrid(Analog&HD-CVI) self-adaptive, 16 IP camera input, up to 5Mp)	22,000,000
Compact 1U 1HDD		<b>AOC</b> HCVR5104HS-S3	4/8ch 1080P 12/15fps per channel, 720P realtime 1 HDMI/1 VGA, 1 Audio in/1 Audio out, 1 RJ45(100M), 1 RS485, 2 USB, 1 HDD, Tribrid(Analog&HD-CVI) self-adaptive, 4+2/8+4 IP camera input, up to 5Mp)	4,100,000
		<b>AOC</b> HCVR5108HS-S3		6,900,000
1U 2HDD		<b>AOC</b> HCVR5216A-S3	16ch 1080P 12/15fps per channel, 720P realtime 1 HDMI/1 VGA, 1 RJ45(1000M), 4 Audio in/1 Audio out, 16 Alarm in/3 Alarm out, 1 RS485, 2 USB, 2 HDD, Tribrid(Analog&HD-CVI) self-adaptive, 16+8 IP camera input, up to 5Mp)	14,300,000
1U 1HDD		<b>AOC</b> HCVR7104H-S2	4/8ch 1080P 25/30fps per channel 1 HDMI/1 VGA, 1 Audio in/1 Audio out, 1 RJ45(100M), 1 RS485, 2 USB, 1 HDD, Tribrid(Analog&HD-CVI) self-adaptive, IP camera input, up to 5Mp)	4,100,000
		<b>AOC</b> HCVR7108H-S2		6,900,000
		<b>AOC</b> HCVR7104HE-S2	4,400,000	
		<b>AOC</b> HCVR7108HE-S2	7,300,000	
<b>AOC=Audio Over Coaxial</b>		<b>Tribrid=CVI/CVBS/IP</b>	<b>Penta-brid=CVI/AHD/TVI/CVBS/IP</b>	

**PAYTAKHTCCTV.COM** **فروشگاه پایتخت**

**@Paytakhtcctv1** / تلگرام: **09336765878** / **021-66348327** راههای ارتباطی ما:



Type	Picture	Model	Main Features	IRR
1U 2HDD		HCVR7208AN-4M	8/16ch 4MP non-realtime, 1 HDMI/1 VGA,16ch Video in,1 RJ45(1000M), 1 Audio in/1 Audio out,1 RS485,2 USB. 2 HDD. Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,8+4/16+8 IP camera input,up to 5Mp)	13,000,000
		HCVR7216AN-4M		18,800,000
2U 8HDD		HCVR7816S	16ch 1080P 25/30fps per channel 2 HDMI/1 VGA, 2 RJ45(1000M), 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Anolog&HD-CVI self-adaptive, 16+16 IP camera input,up to 2Mp 160Mbps )	Call
		HCVR8816S-53		Call
HDCVI Video Converter		TP2105	Self-adaptive output HDCVI, HDMI, VGA, CVBS signal Lossless real time non-compression transmission Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s Fully enclosed dustproof design	3,250,000
UTC Controller		PFM820	Support different formats(HDCVI/AHD/HDTVI/CVBS) switch,which is to satisfy the requirements of different storage deviceenvironments for clients. Various format indicator lights,which makes it convenient forusers to check the current format status and prompt if theformat switch is successful.	560,000



Available on the App Store



GET IT ON Google play

