

Type	Picture	Model	Resolution	Main Features	IRR
Classic Bullet		IPC-HFW1220SP-0360B-S3	2Mega	1/2.9" 2M CMOS,ICR,H.264/MJPEG 1080P(1~30fps) , 3.6mm optional IR 30m,IP67 DC12V/PoE	3,450,000
		IPC-HFW1320SP-0360B-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional, IR 30m,IP67 DC12V/PoE	4,550,000
		IPC-HFW1420SP-0360B	4Mega	1/3" 4M CMOS,ICR,H.264/MJPEG 4MP(1~20fps),3MP/1080P(1~30fps), 3.6mm lens IR 30m,IP67 DC12V/PoE	5,400,000
Long IR Range Bullet		IPC-HFW4431EP-S-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.265/H.264,4MP(1~30fps) 3.6mm lens IR 40m,Micro SD,IP67 DC12V/PoE	8,200,000
Vari-focal Bullet		IPC-HFW2421RP-ZS-IRE6	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m,Micro SD, IP67 DC12V/PoE	9,500,000
Vandal Dome		IPC-HDBW1220EP-0360B-S3	2Mega	1/2.9" 2M CMOS,ICR,H.264/MJPEG 1080P(1~30fps) , 3.6mm optional IR 30m,IP67,IK10 DC12V/PoE	3,550,000
		IPC-HDBW1320EP-0360B-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional, IR 30m,IP67,IK10 DC12V/PoE	4,650,000
		IPC-HDBW1420EP-0360B	4Mega	1/3" 4M CMOS,ICR,H.264/MJPEG 4MP(1~20fps),3MP/1080P(1~30fps), 3.6mm lens IR 30m,IP67,IK10 DC12V/PoE	5,500,000



Type	Picture	Model	Resolution	Main Features	IRR
Long IR Range Eyeball		IPC-HDW4421EP-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.264,4MP(1~20fps) 3.6mm lens IR 50m,IP66 DC12V/PoE	6,300,000
		IPC-HDW4421EMP-AS-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.264,4MP(1~20fps) 3.6mm lens IR 50m,Built-in Mic, Mirco SD,IP67 DC12V/PoE	6,650,000
		IPC-HDW4431EMP-AS-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.265/H.264,4MP(1~30fps) 3.6mm lens IR 50m,Built-in Mic, Mirco SD,IP67 DC12V/PoE	8,450,000
Vari-focal Dome		IPC-HDBW2421RP-ZS	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.264/MJPEG,4MP(1~20fps),3MP/1080P(1~30fps) 2.7-12mm motorized lens IR 30m,Micro SD,IP67,IK10 DC12V/PoE	9,500,000
Indoor PTZ		SD22204T-GN	2Mega 4X	1/2.7" 2Megapixel CMOS Powerful 4x optical zoom Support Triple-streams encoding WDR, Day/Night(ICR), Ultra DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IVS Support PoE Max 100°/s pan speed IP66, IK10	7,600,000
Speed Dome		SD49225T-HN	2Mega 25X	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology Support H.265&H.264 Triple-streams encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P IVS, Support PoE+ IR distance up to 100m IP66	22,500,000
		<b>NEW</b> SD59430U-HNI	4Mega 30X	1/3" 4Megapixel CMOS Powerful 30x optical zoom H.265 Encoding Max. 25/30fps@4M/3M, 25/30/50/60fps@1080P Auto-tracking and IVS Support PoE+ IR distance up to 100m IP66	Call
Cube		<b>PIR</b> IPC-K35AP	3Mega	1/3" 3Megapixel progressive CMOS H.264& MJPEG dual-stream encoding 20fps@3M(2304x1296)&25/30fps@2M (1920x1080) 100° horizontal view angle IR Distance 10m Easy4ip cloud support Micro SD card slot, up to 128GB Alarm in/out,PIR DC12V, PoE	4,500,000



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		NVR2108HS-52	8 Channel H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6Mp resolution preview&playback HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	3,300,000
1U 2HDD		NVR4232	32 Channel H.264 codec decoding Max 200Mbps incoming bandwidth Up to 5Mp resolution preview&playback HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	9,900,000
		NVR4216-4KS2	16/32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	10,500,000
		NVR4232-4K-52		12,000,000
1.5U 4HDD		NVR4432-4K-52		15,800,000
2U 8HDD		NVR4832-4K-52	16/32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	Call
		NVR608-32-4K	384Mbps, Max 12MP, 16ch 1080P decoding, H.264, 1 VGA/2 HDMI(3840x2160), 2 RJ45(1000M), 4 USB(2USB3.0), 1/1ch audio in/out, 8 HDD(6TB each), 1 eSATA, 16/8 alarm in/out, fisheye dewarp, Smart Track, IVS(optional), face detection, RAID0/1/5/6/10/50/60, N+M, ANPR,	33,000,000
		NVR608-32-4KS2	384Mbps, Max 12MP, 16ch 1080P decoding, H.265/H.264, 1 VGA/2 HDMI(3840x2160), 2 RJ45(1000M), 4 USB(2USB3.0), 1/1ch audio in/out, 8 HDD(6TB each), 1 eSATA, 16/8 alarm in/out, fisheye dewarp, Smart Track, IVS(optional), face detection, RAID0/1/5/6/10/50/60, N+M, ANPR,	39,000,000
		NVR608-64-4KS2		Call

Type	Picture	Model	Main Features	IRR
4-Port PoE Switch (Unmanaged)		PFS3005-4P-58	Two-layer PoE Ethernet switch MAC auto study and aging, MAC address list capacity is 1K Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation. Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.	2,160,000
8-Port PoE Switch (Unmanaged)		PFS3110-8P-96	Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Support IEEE802.3af, IEEE802.3at standard Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Industrial wide temperature design	5,000,000
16-Port PoE Switch		PFS4218-16ET-190	Layer 2 management PoE switch PoE budget: 190W Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission PoE management, PoE Setting/Event Statistics/Green PoE Search and upgrade via ConfigTool Support Web management High lightning protection design Non-blocking video transmission	15,500,000
Ultra-HD Network Video Decoder		NVD0405DH-4K	H.265/H.264/MPEG4 video decoding 4ch@12M/4ch@4K/16ch@1080P/64ch@D1 decoding ability 1ch HDMI input, 4ch HDMI/VGA/BNC output, HDMI support Ultra HD 4K output Support up to 4 video-wall display units, support configuration of 1x1,2x1,2x2 Support audio, alarm, bi-directional talk, RS485	Call
Network Keyboard		NKB1000	Keyboard to Control: Dahua High Speed Dome Dahua Standalone DVR Dahua Network High Speed Dome Network Video Server Connection	14,300,000



Available on the  
App Store



Available on  
Google play

