

# فروشگاه پایتخت

مرکز پخش سیستمهای امنیتی و حفاظتی  
تجهیزات نصب و قطعات یدکی

**HIKVISION**



IP Camera

راههای ارتباطی ما

۰۲۱۶۶۳۴۸۳۲۵



۰۲۱۶۶۳۴۸۳۲۷




۰۹۳۳۶۷۵۸۷۸






@paytakhtcctv1

تهران. خیابان جمهوری. نبش شیخ هادی. مجتمع تجاری علاءالدین ۲. طبقه سوم. واحد ۳۱۹






**Network Camera**

No.	Model	Appearance	Description	Price
<b>2 Line Series</b>				
1	DS-2CD2020F-I		*1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE	4.330.000 IRR
3	DS-2CD2042WD-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	6.110.000 IRR
4	DS-2CD2052-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+ Optimized Codec	7.890.000 IRR
5	DS-2CD2120F-I		*1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board	4.330.000 IRR
6	DS-2CD2120F-IS		*1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), -S: Audio/Alarm IO connectors	4.710.000 IRR
7	DS-2CD2142FWD-I		*1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 2.8mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+	6.360.000 IRR
8	DS-2CD2122FWD-IS		*1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/6/2mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec -S: Audio/Alarm IO	6.110.000 IRR
9	DS-2CD2142FWD-IS		*1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 2.8mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm IO*	6.620.000 IRR
10	DS-2CD2152F-IS		*1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm IO*	8.270.000 IRR

Network Camera				
No.	Model	Appearance	Description	Price
<b>2 Line Series</b>				
11	DS-2CD2420F-IW		"1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, -W: Built-in Wi-Fi with WPS"	4.710.000 IRR
12	DS-2CD2442FWD-IW		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+ Optimized Codec	6.490.000 IRR
13	DS-2CD2520F		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Vandal-proof IK10,	4.460.000 IRR

Network Camera				
No.	Model	Appearance	Description	Price
<b>2 Line Series</b>				
14	DS-2CD2620F-IZ		"1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), -Z: Motorized VF lens"	9.610.000 IRR
15	DS-2CD2652F-IS		"1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2560*1920:20fps, 2.8-12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+S: Audio/Alarm IO	15.400.000 IRR
16	DS-2CD2720F-IZ		"1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, -Z: Motorized VF lens"	9.740.000 IRR
	DS-2CD2742FWD-IS		"1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8-12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/Alarm IO	12.980.000 IRR
17	DS-2CD2752F-IS		"1/3" Progressive CMOS, ICR, 0lux with IR, 2560*1920:20fps, 2.8-12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/Alarm IO	14.120.000 IRR

**Network Camera**

No.	Model	Appearance	Description	Price
<b>2 Line Series</b>				
18	<b>DS-2CD2T42WD-I3</b>		*1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -I5: 2pcs EXIR LEDs, up to 30m IR range	<b>6.870.000 IRR</b>
19	<b>DS-2CD2T42WD-I5</b>		*1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -I5: 2pcs EXIR LEDs, up to 50m IR range	<b>7.380.000 IRR</b>
20	<b>DS-2CD2T42WD-I8</b>		*1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -I5: 2pcs EXIR LEDs, up to 80m IR range	<b>8.040.000 IRR</b>
21	<b>DS-2CD2T52-I5</b>		1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+, 2pcs EXIR LEDs, up to 50m range IR	<b>8.650.000 IRR</b>
22	<b>DS-2CD2955FWD-IS</b>		5 MP Network Fisheye Camera • H.265, H.265+, H.264+, H.264 • Support 14 display modes • FOV : horizontal FOV 180°, vertical FOV 180° • Dual video streams • DC12V & PoE (802.3af) • Digital Noise Reduction • Support on-board storage, up to 128 GB • Up to 8m IR range • -S: Audio/Alarm IO	<b>CALL</b>
23	<b>DS-2DE4220IW-DE</b>		2MP 20X Network IR PTZ • 1/2.8" Progressive Scan CMOS • 1920 x 1080 • 20X Optical Zoom • DWDR • 3D intelligent positioning function IRR • Up to 100m IR distance • Support Hik cloud P2P • 12VDC & POE(802.3af) power supply	<b>22.630.000 IRR</b>
24	<b>DS-2DE5220IW-AE</b>		2MP 30X Network IR PTZ Camera • 1/2.8" Progressive Scan CMOS • 1920 x 1080 • 20X Optical Zoom • DWDR • 3D intelligent positioning function • Support Hik cloud P2P • Up to 150m IR distance • Hi-PoE / 24VAC power supply • Support BNC output	<b>31.960.000 IRR</b>
25	<b>DS-2DE7230IW-AE</b>		2MP 30X Network IR PTZ Camera • 1/2.8" Progressive Scan CMOS, up to 1920x1080 • 25 fps at HD1080p • Up to 150m IR distance • 3D DNR, D WDR • 3D intelligent positioning • 30X Optical Zoom • IP66 rating	<b>45.640.000 IRR</b>