













Type	Picture	Model	Resolution	Main Features	IRR
Bullet		HAC-HFW1000RM	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 20m, Smart IR 2.8mm fixed lens	2,200,000
Classic Bullet		HAC-HFW1000S	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	2,700,000
		HAC-HFW1200S	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	3,500,000
		HAC-HFW1220S	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	3,280,000
Classic Bullet		HAC-HFW1200T	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 20m, Smart IR 3.6mm fixed lens	3,200,000
		HAC-HFW1400T	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps 25/30fps@1080P,720P ICR, IP67,DWDR Max. IR Led length: 20m, Smart IR	4,580,000
Pro Series		HAC-HFW2231E	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P. 25/30fps@720P, ICR, IP67, 120db Ture, Max. IR Led 40m, Array LED, Smart IR	7,380,000
Lite Series		HAC-HFW1200B	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Smart IR 3.6mm fixed lens	4,100,000
		HAC-HFW1400B	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps ,25/30fps@1080P,720P ICR, IP67,DWDR Max. IR Led length: 50m, Smart IR	5,560,000
		HAC-HFW1220D	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 80m, Smart IR 3.6mm fixed lens	4,440,000
		HAC-HFW2231D	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P. 25/30 fps@720P, ICR, IP67, Max. IR Led length: 80m, Array LED, Smart IR 3.6mm fixed length	7,980,000
		HAC-HFW1400R-VFS-IRE6	4MP	Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 60m, Smart IR, IP67	8,400,000
		HAC-HFW1220R-VF-IRE6	1080P	1/2.9" 2Megapixel Exmor CMOS, 1080P, ICR, IP67 Max. IR Led length: 60m, Array LED, Smart IR manual vari-focal lens	6,980,000



Type	Picture	Model	Resolution	Main Features	IRR
Classic Dome		HAC-HDW1000M	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	2,240,000
		HAC-HDW1200M	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	3,200,000
Pro Series		 HAC-HDW1200EM-A	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	3,950,000
		 HAC-HDW1220EM-A	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	3,520,000
		HAC-HDW2231EM	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30fps@720P, ICR, IP67, 120db Ture Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length, All Metal	7,450,000
		 HAC-HDW1400EM-A	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps 25/30fps@1080P,720P ICR, IP67, Max. IR Led length: 50m, Smart IR Bulit-in Mic, All Metal	5,120,000
Lite H.265 Series		HAC-HDBW1220R-VF	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67, IK10 Max. IR Led length: 30m, Array LED, Smart IR manual vari-focal lens	6,770,000
		HAC-HDBW2231R-Z	Starlight 1080P	Starlight, 120dB true WDR, 3DNR Max 30fps@1080P HD and SD output switchable motorized lens Max. IR length 30m, Smart IR IP67, IK10, DC12V	Call
		HAC-HDBW1400R-VFS	4MP	Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 30m, Smart IR, IP67, IK10, DC12V	8,240,000
Vari-focal Dome		HAC-HDBW3802E-Z	8MP WDR	1/2" 8Megapixel progressive scan CMOS 3x optical motorized zoom lens Max. 15fps@3840x2160 120db true WDR,2D&3D NR Max.50m IR distance,smart IR, IP67&IK10 Dual voltage input(DC 12v±25%/AC 24V±25%)	2,000,000



Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Bullet		HAC-HFW3231E-Z	Starlight 1080P	1/2.8" 2.1Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Star Light, 120dB True WDR, ICR, IP67 Max. IR Led length: 50m, Smart IR 2.7-12mm auto-iris motorized lens DC12V/AC24V, audio in	Call
		HAC-HFW3802E-Z	8MP WDR	1/2" 8Megapixel progressive scan CMOS 3x optical motorized zoom lens Max. 15fps@3840x2160 120db true WDR, 2D&3D NR Max.100m IR distance, smart IR IP67/IK10 ingress protection Dual voltage input(DC 12v±25%/AC 24V±25%)	2,000,000
Pro Series 4K		NEW  HAC-HFW2802E-A	8MP Starlight	1/2.9" 6Megapixel progressive scan CMOS Max. 20fps@3840x2160 120db true WDR, 2D&3D NR 0.005Lux/F1.6, 30IRE, 0Lux IR on Max.40m IR distance, smart IR, IP67&IK10, Built-in Mic	9,960,000
		NEW  HAC-HFW2601EP-A	6MP WDR	1/2.9" 6Megapixel progressive scan CMOS Max. 20fps@3096x2202 120db true WDR, 2D&3D NR Max.50m IR distance, smart IR, IP67&IK10, Built-in Mic	9,050,000
Pro S Series 4K		NEW  HAC-HDW2802T-A	8MP Starlight	1/2" 8Megapixel progressive scan CMOS Max. 15ps@4K, 20fps@3840x2160 120db true WDR, 2D&3D NR Max.50m IR distance, smart IR 0.01Lux/F1.9(Color) 0Lux/F1.9(IR on), IP67&IK10 Lens 3.6mm	9,960,000
		NEW HAC-HDW2601T-A	6MP WDR	1/2.9" 6Megapixel progressive scan CMOS Max. 20fps@3096x2202 120db true WDR, 2D&3D NR Max.50m IR distance, smart IR, 0.01Lux/F1.9(Color) 0Lux/F1.9(IR on), IP67&IK10 Dual voltage input(DC 12v±25%/AC 24V±25%), Lens 3.6mm	9,050,000
Pro Seies 6MP		NEW  HAC-HDW2601T-Z-A	6MP WDR	1/2.9" 6Megapixel progressive scan CMOS Max. 20fps@3096x2202 120db true WDR, 2D&3D NR Max.60m IR distance, smart IR 0.01Lux/F1.6(Color) 0Lux/F1.6(IR on), IP67&IK10 Lens 2.7-13.5mm, Motorized	13,470,000
		NEW HAC-HDBW2601R-Z	6MP WDR	1/2.9" 6Megapixel progressive scan CMOS Max. 20fps@3096x2202 120db true WDR, 2D&3D NR Max.30m IR distance, smart IR 0.01Lux/F1.3, 30IRE 0Lux(IR on) IP67&IK10, Lens 2.7-13.5mm, Motorized	13,470,000
Speed Dome		SD49225I-HC	1080P 25x Starlight IR PTZ	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 100m, IP66	39,840,000
		SD59230I-HC	2MP 30x Starlight IR PTZ	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 30x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 150m, IP66	71,700,000
		SD59430I-HC	4MP 30x IR PTZ	1/3" 4Megapixel CMOS Powerful 30x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P IR distance up to 100m, IP66	71,700,000







Available on the App Store











GET IT ON Google play



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid XVR4104HS-S2	4CH:1080N/720P (1~25/30fps) 8/16CH:1080N(1~12fps)/720P(1~15fps) Support HDCVI/AHD/TVI/CVBS/IP video inputs 4+1: each channel up to 2MP , 8+2/16+2:each channel up to 5MP & Coax Audio , 1 HDMI/1 VGA, 1 Audio in/1 Audio out,1 RJ45(100M),up to 8TB	6,150,000
		AOC Penta-brid XVR4108HS-S2		7,900,000
		AOC Penta-brid XVR4116HS-S2		13,700,000
1U 1HDD		AOC Penta-brid XVR4216A-S2	16ch 1080N(1~12fps)/720P(1~15fps) 1 HDMI/1 VGA,,4 Audio in/1 Audio out,16 Alarm in/3 Alarm out,1 RJ45(100M),1 RS485,2 USB,2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+2 IP camera input,up to 5Mp & Coax Audio	19,700,000
Compact 1U 1HDD		AOC Penta-brid XVR5104HS-S2	4/8 ch 4M-N /1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2/8+4 Channel, each channel up to 5MP Long transmission distance over coax cable & Coax Audio	7,720,000
		AOC Penta-brid XVR5108HS-S2		12,230,000
1U 2HDD		Penta-brid XVR5216AN-S2	16ch 4M-N /1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/3 Alarm out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+8 IP camera input,up to 5Mp) Long transmission distance over coax cable & Coax Audio	23,640,000
		AOC Penta-brid XVR5232AN-S2	32ch 4M-N /1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 IP camera input,up to 5Mp) Long transmission distance over coax cable & Coax Audio	41,500,000
		AOC Penta-brid XVR5208AN-4KL	8ch 4K(1~7fps) ,5MP(1~12fps) 4M-N /1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,8+4 IP camera input,up to 8Mp) Long transmission distance over coax cable & Coax Audio	23,300,000
AOC=Audio Over Coaxial		Tribrid=CVI/CVBS/IP	Penta-brid=CVI/AHD/TVI/CVBS/IP	



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid XVR5104HS-4M	4MP/3MP(1~15fps), 1080P@25/30fps, 720P@50/60fps 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2 Channel, each channel up to 5MP, Coax Audio	10,800,000
		AOC Penta-brid XVR5108HS-4KL	8 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP)8+4 Channel, each channel up to 8MP, Coax Audio	15,900,000
1U 2HDD		AOC Penta-brid XVR5216AN-4KL	16 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2USB,2HDD (CVBS/HD-CVI/AHD/TVI/IP)16+8 Channel, each channel up to 8MP, Coax Audio	31,300,000
2U 8HDD		XVR8816	16ch 4M 10/15 fps & 1080P 25/30 fps per channel 2 HDMI/1 VGA,2 RJ45(1000M). 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Anolog&HD-CVI-AHD-TVI self-adaptive,16+48 IP camera input,up to 12Mp 384Mbps) People Counting , HeatMap ,	Call
1U 1HDD		XVR5232AN-S2	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,4 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 Channel, each channel up to 5MP)	41,500,000
1.5U 4HDD		XVR5432L	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,4 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 Channel, each channel up to 5MP)	80,600,000
2U 8HDD		XVR5832S	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M). 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 8 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 Channel, each channel up to 5MP)	Call
1.5U 4HDD		XVR7416L	16ch 1080P 25/30fps per channel, 720P realtime 2 HDMI/1 VGA,1 RJ45(1000M), 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 4 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+8 IP camera input,up to 5Mp	59,800,000
2U 8HDD		HCVR8816	16ch 1080P 25/30fps per channel 2 HDMI/1 VGA,2 RJ45(1000M). 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Anolog&HD-CVI-AHD self-adaptive,16+48 IP camera input,up to 12Mp 256Mbps) People Counting , HeatMap ,	121,000,000
AOC=Audio Over Coaxial		Tribrid=CVI/CVBS/IP	Penta-brid=CVI/AHD/TVI/CVBS/IP	



Type	Picture	Model	Main Features	IRR
Alarm Box		NEW DHI-ARB1606	Support through RS485 access to the back-end storage Support 16ch Alarm In/6ch Alarm Out interface Support 2-bit DIP switch (0/1) to determine the different alarm box access; Max support 4 alarm boxes having access to the back-end storage device Linked configuration alarm to DVR	3,740,000
HDCVI Distributor		TP2600	Support 1/3 channel In/Out Lossless non-compression transmission Support video format as 25/30/50/60fps@720P & 25/30fps@1080P UPnP, easy installation LED indicators	3,970,000
UTC Controller		PFM820	Support different formats(HDCVI/AHD/HDTV/CVBS)switch,which is to satisfy requirements of different storage deviceenvironments for clients.	Call
Wall mount		PFB203W	HDBWxxR-Z/VF/E/F,HDWxxR-Z/VF/EM/E/S ,EB Material: Aluminum Wall Mount Bracket	940,000
Junction box		PFA121	HFVxxEZ/E Series Material: Aluminum IP66 Junction Box	1,600,000
		PFA134	HFVxxS ,HFVxxT,HFVxxSL,HFVxxRM,HFVxxR Series Material: Aluminum IP66 Junction Box	670,000
		PFA135	HFVxxR-Z/VF,HFVxxB,HFVxxD Series Material: Aluminum IP66 Junction Box	530,000
		PFA137	HDBWxxR-Z/VF , HDWxxR-Z,SD22 Series Material: Aluminum IP66 Junction Box	670,000
		PFA139	HDBWxxF , HDWxxEM Series Material: Aluminum IP66 Junction Box	730,000
Pole mount		PFA152-E	PFB203W,PFA121,PFA134,PFA135,PFA137+ PFA152-E Pole mount Material: Aluminum	2,140,000
Passive HDCVI Balun		NEW PFM800-4M	1 Channel Passive HDCVI BalunReal-time transmission over UTP CAT5E/6 cable. Passive, no need for power supply. With female BNC connector, and pluggable screw terminal connections.	530,000
POC Transceiver		PFM810	Power supply: Input voltage DC24-36V, can provide DC12V 9W(max) power supply to remote cameras, simplify engineering wiring Transmission distance: 400m (max) Main functions: Use single coaxial cable real-time transmit 1-ch HD video signal and 1-ch DC power	2,000,000

